

WORM DRIVE & SCREW CLAMPS



Continuous Worm Drive Kit

HCL offers a high strength worm drive kit, comprising of a 14mm wide perforated band with a separate screw and housing. The band can be cut to a desired length and fitted using standard tools, thereby offering a versatile clamping solution.

All the components are made from W4 SS304, providing excellent weathering and chemical resistance.

Applications

- Electrical Exhaust Fans
- Flexible Ducting
- HVAC
- Sign Fixing
- General Industry

| PERFORMANCE | Strength | <div><div></div><div></div><div></div></div> |
|-------------|---------------|--|
| | Temperature | <div><div></div><div></div><div></div></div> |
| | Speed | <div><div></div><div></div><div></div></div> |
| | Weathering | <div><div></div><div></div><div></div></div> |
| | Chemical | <div><div></div><div></div><div></div></div> |
| | Dynamic Range | <div><div></div><div></div><div></div></div> |

Materials – see section 10.3

- W4 304 SS

Installation Tools – see section 9.1



MT-D-01

MT-AD-01

MT-TD-01

| HCL Part No | | Band Width mm | Band Thickness mm | Hex Screw A/F mm | Band Reel Lengths m | Screw/Housing Box Quantity |
|-------------|---------------|---------------|-------------------|------------------|---------------------|----------------------------|
| Band | Screw/Housing | | | | | |
| FC-BA-25M | FC-BU | 14 | 0.8 | 8.0 | 25 | 25 |

All weights, dimensions & quantities are subject to a 2.5% tolerance.
To add material selection to the HCL Part No: for W4, add "W4".