

# CABLE RETENTION



## Metal Cable Tie – Re-usable – Coated

These re-usable Cable ties have a thick PPA coating, which removes all sharp edges; thus protecting both the fitter and the application.

They are halogen free, flame retardant and extremely non-corrosive, making them highly suited to aggressive environments, such as marine cable bundling.

PERFORMANCE	Strength	<div><div></div><div></div><div></div></div>
	Temperature	<div><div></div><div></div><div></div></div>
	Speed	<div><div></div><div></div><div></div></div>
	Weathering	<div><div></div><div></div><div></div></div>
	Chemical	<div><div></div><div></div><div></div></div>
	Dynamic Range	<div><div></div><div></div><div></div></div>

### Applications

- Chemical Industry
- Offshore
- Fixing Identification
- Shipyards

### Certifications



### Materials – see section 10.3

- W5** 316 SS with PPA coating

### Installation Tools – see section 9.1



MT-MCT-01

HCL Part No	Max Diameter mm	Length mm	Band Width mm	Band Thickness mm	Bag Quantity pcs
RCT-6.4-152	38	152	6.4	1.3	100
RCT-6.4-229	63	229			
RCT-6.4-305	86	305			
RCT-6.4-457	137	457			
RCT-6.4-610	185	610			
RCT-6.4-762	231	762			
RCT-6.4-914	280	914			
RCT-9.5-152	38	152	9.5		
RCT-9.5-229	63	229			
RCT-9.5-305	86	305			
RCT-9.5-457	137	457			
RCT-9.5-610	185	610			
RCT-9.5-762	231	762			
RCT-9.5-914	280	914			

All weights, dimensions & quantities are subject to a 2.5% tolerance.  
To add material selection to the HCL Part No: for W5 with PPA coating, add "W5-PPA".